

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A safety needle assembly comprising  
a needle hub with proximal and distal ends and a passage extending between said ends,  
a needle cannula mounted to said passage of said needle hub and having a pointed distal  
end projecting beyond said distal end of said hub,  
a shield having proximal and distal ends, said proximal end of said shield being hingedly  
mounted to said hub for rotation from a first position where said shield is spaced from said  
needle cannula to a second position where said shield substantially shields said needle cannula,  
said shield comprising at least one support wall, and a channel mounted to said support wall, said  
channel having a top wall and opposed first and second sidewalls extending from said top wall,  
and at least one resiliently deflectable cannula finger lock projecting from said first sidewall  
angularly toward said top wall, ~~said cannula finger lock deflecting during rotation of said shield  
toward said second position for trapping said needle cannula~~  
wherein said channel can be selectively mounted to said support wall in one of a plurality of  
orientations in relation to one another.

2. (Original) The safety shield assembly of claim 1, wherein said needle hub comprises  
an inner tubular portion securely mounted to said needle cannula and an outer collar securely  
mounted over said inner tubular portion, said shield being hingedly mounted to said collar of said  
hub.

3. (Original) The safety needle assembly of claim 1, wherein said needle cannula includes  
a proximal end, said needle cannula extending entirely through said passage of said hub such that  
said proximal end of said needle cannula projects proximally beyond said proximal end of said  
hub.

4. (Original) The safety needle assembly of claim 3, further comprising an elastomeric  
sleeve mounted over said proximal end of said needle cannula and securely engaged to said

proximal end of said hub.

5. (Currently Amended) ~~The safety needle assembly of claim 1,~~ A safety needle assembly comprising

a needle hub with proximal and distal ends and a passage extending between said ends,  
a needle cannula mounted to said passage of said needle hub and having a pointed distal  
end projecting beyond said distal end of said hub,

a shield having proximal and distal ends, said proximal end of said shield being hingedly  
mounted to said hub for rotation from a first position where said shield is spaced from said  
needle cannula to a second position where said shield substantially shields said needle cannula,  
said shield comprising at least one support wall, and a channel mounted to said support wall, said  
channel having a top wall and opposed first and second sidewalls extending from said top wall,  
and at least one resiliently deflectable cannula finger lock,

wherein said top wall of said channel comprises mounting structure for mounting said channel to said support wall, ~~said channel having opposite first and second longitudinal ends, said mounting structure being closer to said first end of said channel than to said second end,~~ whereby said channel can be disposed in either a first rotational orientation or in a second rotational orientation relative to said ~~proximal end and said distal end of said shield~~ support wall for altering positions of said channel relative to ~~said shield and~~ said needle cannula.

6. (Original) The safety needle assembly of claim 5, wherein said support wall has a distal end remote from said proximal end of said shield, said channel being dimensioned such that, in said second rotational orientation of said channel relative to said support wall, said second end of said channel projects distally beyond said distal end of said support wall.

7. (Original) The safety needle assembly of claim 6, wherein said channel is dimensioned such that in said first rotational orientation, said first end of said channel substantially aligns with said distal end of said support wall.

8. (Original) The needle assembly of claim 7, wherein said channel is dimensioned such that in said first rotational orientation, said second end of said channel is substantially adjacent

said proximal end of said shield.

9. (Original) The safety needle assembly of claim 5, wherein said at least one cannula finger lock comprises a plurality of cannula finger locks, a first of said cannula finger locks being substantially adjacent said first end of said channel and a second of said cannula finger locks being substantially adjacent said second end of said channel.

10. (Original) The safety needle assembly of claim 1, wherein said support wall comprises a plurality of apertures extending therethrough, said channel having a plurality of mounting projections formed thereon, said mounting projections being dimensioned and disposed for locked engagement with said apertures in said support wall.

11. (Original) The safety needle assembly of claim 1, wherein portions of said shield adjacent said proximal end are configured for partly surrounding said hub, said support wall extending substantially rigidly from said portions of said shield dimensioned for partly surrounding said hub.

12. (Original) The safety needle assembly of claim 1, wherein said channel has an elongate convexly arcuate outer surface, said support wall having a concave surface for closely receiving said convex outer surface of said channel.

13. (Original) The safety needle assembly of claim 1, further comprising a medical device connected to said needle hub.

14. (Original) The safety needle assembly of claim 13, wherein the medical device comprises a holder for releasably receiving a fluid collection tube.

15. (Original) The safety needle assembly of claim 13, wherein the medical device is a syringe.

16. (Original) The safety needle assembly of claim 13, wherein the medical device comprises an intravenous infusion set.

17. (Currently Amended) A safety needle assembly comprising  
a needle hub with proximal and distal ends and a passage extending between said ends,  
a needle cannula mounted to said passage of said needle hub and having a pointed distal  
end projecting beyond said distal end of said hub,  
a shield having proximal and distal ends, said proximal end of said shield being hingedly  
mounted to said hub for rotation from a first position where said shield is spaced from said  
needle cannula to a second position where said shield substantially shields said needle cannula,  
said shield comprising at least one support wall, a channel mounted to said support wall, said  
channel having a top wall and opposed first and second sidewalls extending from said top wall,  
at least one cannula finger lock projecting from said first sidewall angularly toward said top wall,  
~~said cannula finger lock being configured for trapping said needle cannula in response to rotation  
of said shield toward said second position~~  
wherein said support wall comprises at least one aperture extending therethrough, said channel  
having at least one mounting projection formed thereon, said at least one mounting projection  
being dimensioned and disposed for locked engagement with said at least one aperture in said  
support wall.

Claims 18 to 21 (Cancelled)

22. (Currently Amended) The safety needle assembly of claim 17, wherein said at least  
one cannula finger lock comprises a plurality of cannula finger locks, ~~a first of said cannula  
finger locks being substantially adjacent said first end of said channel and a second of said  
cannula finger locks being substantially adjacent said second end of said channel.~~

23. (Previously Presented) The safety needle assembly of claim 17, wherein said support  
wall comprises a plurality of apertures extending therethrough, said channel having a plurality of  
mounting projections formed thereon, said mounting projections being dimensioned and  
disposed for locked engagement with said apertures in said support wall.

24. (Previously Presented) The safety needle assembly of claim 17, wherein portions of said shield adjacent said proximal end are configured for partly surrounding said hub, said support wall extending substantially rigidly from said portions of said shield dimensioned for partly surrounding said hub.

25. (Previously Presented) The safety needle assembly of claim 17, wherein said channel has an elongate convexly arcuate outer surface, said support wall having a concave surface for closely receiving said convex outer surface of said channel.

26. (New) The safety needle assembly of claim 5, wherein said channel further comprising first and second longitudinal ends, said mounting structure being closer to said first end of said channel than to said second end.